

Philips
Stereo dubbing cable

6 ft

3.5 mm (M) - 3.5 mm (M)

SWA2162W



Ensure a reliable connection

with this stereo dubbing cable

Depend on this cable to provide you with a reliable audio connection between components.

Enjoy good audio quality

- Nickel-plated connectors for reliable contact
- High purity copper conductor for reliable signal transfer

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket

Protects against signal loss

- Bare copper shielding

PHILIPS
sense and simplicity

Stereo dubbing cable
6 ft 3.5 mm (M) - 3.5 mm (M)

Specifications

Inner Carton

- Gross weight: 0.318 kg
- Gross weight: 0.7 lb
- GTIN: 2 06 09585 16308 3
- Inner carton (L x W x H): 8 x 3.5 x 5.75 inch
- Inner carton (L x W x H): 20.3 x 8.9 x 14.6 cm
- Nett weight: 0.177 kg
- Nett weight: 0.39 lb
- Number of consumer packagings: 6
- Tare weight: 0.141 kg
- Tare weight: 0.31 lb

Outer Carton

- Gross weight: 4.468 kg
- Gross weight: 9.85 lb
- GTIN: 1 06 09585 16308 6
- Outer carton (L x W x H): 16.5 x 16 x 9.75 inch
- Outer carton (L x W x H): 41.9 x 40.6 x 24.8 cm
- Nett weight: 2.123 kg

- Nett weight: 4.68 lb
- Number of consumer packagings: 72
- Tare weight: 2.345 kg
- Tare weight: 5.17 lb

Packaging dimensions

- Packaging dimensions (W x H x D): 7.0 x 19.7 x 2.5 cm
- Packaging dimensions (W x H x D): 2.75 x 7.75 x 1 inch
- Gross weight: 0.037 kg
- Gross weight: 0.082 lb
- Nett weight: 0.065 lb
- Nett weight: 0.029 kg
- Number of products included: 1
- Packaging type: Blister
- Tare weight: 0.017 lb
- Tare weight: 0.008 kg
- UPC: 6 09585 16308 9

SWA2162W/27

Product highlights

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.



Issue date 2008-10-29

Version: 1.1.6

12 NC: 8670 000 47877
UPC: 6 09585 16308 9

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com